

# ROSO Interior panel



Feel the texture of the wood as you run your fingers over its fine lines, coarse surface, and raised spots. These features tell the unique story of the tree from which the wood originated. The ROSO interior panels provide an authentic tactile experience.

more informaton:

<https://www.siparila.com/en/product/roso-interior-panel/>

**SIPARILA**

WITH WOOD, YOU CREATE UNIQUE LIVING ENVIRONMENTS  
WWW.SIPARILA.COM

# ROSO Interior panel

The ROSO panels are suitable for both walls and ceilings in dry and moist conditions. The panels are end-matched, reducing material loss and enabling flexible installation. It is important to paint cut surfaces to prevent panels from cracking. The installing waste is 5-10 percent.

The ROSO panels should meet the following criteria:

- Knots can be a maximum of 50% of the width of the panel.
- The panel can have a 30 mm reaction on the edge in a two-meter distance, a 4 mm reaction on the side in a two-meter distance, and a 20 mm twisting in a two-meter distance.
- Resin pockets and heart lines are allowed. Wood reactions are permitted as long as they do not hinder the fastening of the panels.


**Pure white**



**Black**



## Product info:



Product code	Thickness	Width	Length	Open seam	Coverage	Color	Yield
ROSOB13X120PIFWP235	13 mm	120 mm	2350 mm	3 mm	107 mm	Pure white	9,34 m/m <sup>2</sup>
ROSO13X120PIF3205	13 mm	120 mm	2050 mm	3 mm	107 mm	Black	9,34 m/m <sup>2</sup>
ROSO13X120PIF3235	13 mm	120 mm	2350 mm	3 mm	107 mm	Black	9,34 m/m <sup>2</sup>

Instructions for installation: [www.siparila.com](http://www.siparila.com)