

DECLARATION OF PERFORMANCE

The undersigned, representing
Siparila Oy (Varaslahdentie 1, 40800 Vaajakoski, Finland)
hereby declares that the

SOLID WOOD PINE PANELING WITH SURFACE COATING

is in conformity with the provisions of the EC Regulation No 305/2011 Construction Product
Regulation system of assessment and verification of constancy of performance:

System 1


and is in accordance with the requirements of

EN 14915:2013

Notified body Inspecta Sertifiointi Oy (No. 0416) conducts continuous monitoring of the factory's
internal quality control and issues factory quality control certificates 0416-CPR-7455, 7326 and 10951.

CHARACTERISTIC	PERFORMANCE DECLARATION
Species	Scots pine (Pinus sylvestris)
Intended use	For interior use
Density and range of thickness/minimum thickness	460 kg/m ³ , >14 mm/8 mm
Reaction to fire	B-s1, d0
Emission of formaldehyde	E1
Content of Pentaclorophenol	NPD
Release of other dangerous substances	NPD
Water vapor permeability	NPD
Thermal resistance	0,10 W/(m K)
Sound absorption	NPD
Biological durability (according to CEN/TS 15083-1:2005)	Class 4

Mounted to the product with A1 or A2-s1,d0 classification.
Installation of panels mechanically without studs. Valid for vertical and horizontal arrangements.



Juha Sojakka
CEO
Vaajakoski 25.11.2024