

## DECLARATION OF PERFORMANCE

The undersigned, representing  
Siparila Oy (Varaslahdentie 1, 40800 Vaajakoski, Finland)  
hereby declares that the

### SOLID WOOD SPRUCE CLADDING AND PANELING WITH FIRE RETARDANT COATING

is in conformity with the provisions of the EC Regulation No 305/2011 Construction Product  
Regulation system of assessment and verification of constancy of performance:

System 1

and is in accordance with the requirements of

EN 14915:2013

Notified body Kiwa Sertifiointi Oy (No. 0416) conducts continuous monitoring of the factory's internal  
quality control and issues factory quality control certificates 0416-CPR-7455, 7326 and 10951.

CHARACTERISTIC	PERFORMANCE DECLARATION
Species	Spruce (Picea abies)
Intended use	For exterior use
Density and range of thickness	390 kg/m <sup>3</sup> , 18-52mm
Reaction to fire	B-s1, d0
Emission of formaldehyde	E1
Content of Pentachlorophenol	NPD
Release of other dangerous substances	NPD
Water vapor permeability	NPD
Thermal resistance	0,13 W/(m K)
Sound absorption	NPD
Biological durability (according to CEN/TS 15083-1:2005)	Class 4



Janne Seilo  
CEO  
Vaajakoski 28.11.2025