

DECLARATION OF PERFORMANCE

The undersigned, representing
Siparila Oy (Varaslahdentie 1, 40800 Vaajakoski, Finland)
hereby declares that the

THERMALLY MODIFIED SOLID WOOD SPRUCE CLADDING AND PANELING WITHOUT SURFACE COATING

is in conformity with the provisions of the EC Regulation No 305/2011 Construction Product
Regulation system of assessment and verification of constancy of performance:

System 3

and is in accordance with the requirements of

EN 14915:2013

Notified body Meža un koksnes produktu pētniecības un attīstības institūts (No. 2040) performed the
initial type testing under system 3 and issued the test reports.

CHARACTERISTIC	PERFORMANCE DECLARATION
Species	Spruce (Picea abies)
Intended use	For exterior use
Width range	35–225 mm
Density and range of total/minimum thickness	400 kg/m ³ , ≥17/9 mm
Installation direction	Horizontal and vertical
Reaction to fire	D-s2, d0
Emission of formaldehyde	E1
Content of pentachlorophenol	NPD
Release of other dangerous substances	NPD
Water vapor permeability	NPD
Thermal resistance	0,11 W/(m K)
Sound absorption	NPD
Biological durability (according to CEN/TS 15083-1:2005)	Class 1, when thermally modified (215 °C, Intense)



Juha Sojakka
CEO

Vaajakoski 16.10.2024