

DECLARATION OF PERFORMANCE

The undersigned, representing
Siparila Oy (Varaslahdentie 1, 40800 Vaajakoski, Finland)
hereby declares that the

THERMALLY MODIFIED SPRUCE CLADDING AND PANELING WITH FIRE IMPREGNATION

is in conformity with the provisions of the EC Regulation No 305/2011 Construction Product
Regulation system of assessment and verification of constancy of performance:

System 1

and is in accordance with the requirements of

EN 14915:2013

Notified body Kiwa Sertifiointi Oy (No. 0416) conducts continuous monitoring of the factory's internal
quality control and issues factory quality control certificates 0416-CPR-7455, 7326 and 10951.

| CHARACTERISTIC | PERFORMANCE DECLARATION |
|--|--|
| Species | Spruce (Picea abies) |
| Intended use | For exterior use |
| Density and range of thickness | 314-434 kg/m ³ , 15-42 mm |
| Reaction to fire | B-s1, d0 |
| Emission of formaldehyde | E1 |
| Content of Pentaclorophenol | 0 ppm |
| Release of other dangerous substances | NPD |
| Water vapor permeability | Density kg/m ³ 450-700: Wet 20-50 / Dry: 50-200 |
| Thermal resistance | 0,13 W/(m K) |
| Sound absorption | 250 Hz – 500 Hz: 0,1 / 1000 Hz – 2000 Hz: 0,3 |
| Biological durability (according to CEN/TS 15083-1:2005) | Class 1 |



Janne Seilo
CEO
Vaajakoski 28.11.2025